

INSTALL | 1387 TUBES

Nominal Size	Approx OD	MEDIUM			HEAVY		
		O/D Max	O/D Min	Thickness	O/D Max	O/D Min	Thickness
8	13.5	13.9	13.3	2.3	13.9	13.3	2.9
10	17.2	17.4	16.8	2.3	17.4	16.8	2.9
15	21.3	21.7	21.1	2.6	21.7	21.1	3.2
20	26.9	27.2	26.6	2.6	27.2	26.6	3.2
25	33.7	34.2	33.4	3.2	34.2	33.4	4.0
32	42.4	42.9	42.1	3.2	42.9	42.1	4.0
40	48.3	48.8	48	3.2	48.8	48	4.0
50	60.3	60.8	59.8	3.6	60.8	59.8	4.5
65	76.1	76.6	75.4	3.6	76.6	75.4	4.5
80	88.9	89.5	88.1	4.0	89.5	88.1	5.0
100	114.9	114.9	113.3	4.5	114.9	113.3	5.4
125	139.7	140.6	138.7	5.0	140.6	138.7	5.4
150	165.1	166.1	164.1	5.0	166.1	164.1	5.4

All dimensions above are shown in mm.

Install is manufactured fully in accordance with BS 1387 and ISO 65.

Light weight tubes are also available (equivalent to ISO 65 light series II).